



## TRAVI HEA

S275JR/S355J2

TRAVI HEA	BASE	ALTEZZA	SP. ASTA	SP. ALI	KG / ML.
100	99	96	5,0	8,0	16,7
120	119	114	5,0	8,0	19,8
140	138	133	5,5	8,5	24,7
160	157	150	6,0	9,0	30,4
180	177	172	6,5	10,0	35,5
200	197	190	7,0	11,0	42,3
220	217	211	7,25	11,5	50,5
240	237	230	7,75	12,5	60,3
260	257	250	8,0	13,0	68,2
280	277	267	8,25	13,5	76,4
300	297	289	8,25	14,5	88,3
320	310	300	9,0	15,5	97,6

**DISPONIBILI LUNGHEZZE 6 E 12 MT**

**POSSIBILITA' DI TAGLIO A MISURA**

## TABELLE PORTATE E SOLLECITAZIONI

<b>PORTATA HEA SOLL. A FLESSIONE IN Q.LI</b>										
<b>DISTANZA TRA GLI APPOGGI IN METRI</b>										
	3	4	5	6	7	8	9	10	11	12
100	30	22	18	14						
120	44	33	26	21	18					
140	65	48	38	31	26	23				
160	93	69	55	45	38	33	28	25		
180	124	92	73	60	51	44	38	34	30	
200	165	123	97	80	68	59	51	45	40	36
220	218	163	129	107	91	78	68	61	54	49
240	286	214	170	140	119	103	90	80	72	65
260	354	265	210	174	148	128	113	100	90	81
280	428	320	255	210	179	155	137	121	109	98
300	535	400	318	263	224	194	171	152	137	124
320	628	463	374	310	263	229	201	180	161	146

<b>PORTATA HEA SOLL. A COMPRESSIONE IN Q.LI</b>										
<b>ALTEZZA DEI PILASTRI IN METRI</b>										
	3	3,5	4	4,5	5	5,5	6	6,5	7	8
100	184	159	137	111	91	75	63			
120	251	227	201	179	156	128	108	92		
140	337	313	284	260	234	210	184	156	135	
160	440	411	385	355	323	296	269	245	213	
180	537	510	480	450	424	392	360	331	306	244
200	657	628	598	566	534	503	468	435	404	348
220	804	768	740	709	672	639	605	565	533	463
240	975	945	903	871	842	803	763	723	679	611
260	1120	1085	1044	1021	978	945	902	863	822	743
280	1276	1235	1197	1162	1128	1089	1045	1011	967	879
300	1488	1440	1406	1374	1323	1295	1250	1200	1169	1065
320	1645	1592	1555	1519	1463	1432	1382	1327	1292	1178